INDUSTRIAL COMPONENT DATA

HC-M-B06-MFH-B 1182085 PHOENIX CONTACT Module Support Frame HC-M-B06-MFH-B

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-B06-MFH-B



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-B06-MFH-B
Catalog number	1182085
Category	Module carrier frame for industrial connectors
Minimum order	1 Pcs
Document ID	EO-12EF7EEB79
Generated	2026-11-18

Product Overview

Module Support Frame - HC-M-B06-MFH-B
Frame for module support, size: B6, type: for recessed side (a, b, c, ...), 4 mm² ... 6 mm², application: Frame for module support
Module frames, dimensions: B6, design: per flush-mounted side (a, b, c, ...), 4 mm2 ... 6 mm2, application: Module frames

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral notes This product replaces item 1417398 HC-M-B06-MF-B
Article featuresProduct Type Module frames
Series HC-M-B
HC-M-02
HC-M-03
HC-M-03/04
HC-M-04
HC-M-05
HC-M-06
HC-M-08
HC-M-08-GBIT
HC-M-12

HC-M-17
HC-M-20
HC-M-25
HC-M-DSUB
HC-M-EMV
HC-M-HV
HC-M-HS
HC-M-00
Application Module frames
type B6
Number of module connection points 2
Execution for flush-mounted side (A, B, C, ...)
Frame type Module frames
Data maintenance status
Article review 03
Connection dataConductor connection
Connection section 4 mm² ... 6 mm² (for PE conductor - power side)
1 mm² ... 2.5 mm² (For PE conductor - controller side)
AWG Connection Section 12 ... 10 (for PE conductor - power side)
18 ... 14 (For PE conductor - controller side)
Tightening torque 0.5 Nm ... 0.8 Nm (Fixing screws for mounting in the HEAVYCON enclosure)
dimensionsDimensioned Drawing
width 34.9 mm
height 36 mm
length 51 mm
Material informationContact Insert Material Zinc Die Cast Alloy
Mechanical characteristicsMechanical data
Manoeuvring cycles >= 500
Environmental and electrical life conditionsEnvironmental conditions
Ambient temperature (operating) -40 °C ... 125 °C
MontageMounting Note HC-MHR-PE16 (1636981) for PE connection extension to 16 mm².
Use suitable end protectors (PE connection screws without wire protection) with PE wires, max. thread length of the screw connection 12 mm in cases without pins with side exit
When inserting the module frame into metal enclosures, the connection of the PE protect...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-B06-MFH-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.