INDUSTRIAL COMPONENT DATA

# HC-STA-B48-HHFS-5TTM25-EM-AL 1345274 PHOENIX CONTACT B48 overhead housing, for longitudinal flange, material..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-B48-HHFS-5TTM25-EM-AL**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | HC-STA-B48-HHFS-5TTM25-EM-AL |
| Catalog number | 1345274 |
| Category | Housing for rectangular connectors |
| Minimum order | 1 Pcs |
| Document ID | EO-11F5E0F357 |
| Generated | 2026-11-19 |

## Product Overview

B48 overhead housing, for longitudinal flange, material: Die-cast aluminium, seawater resistant, cable outlets: 5, straight, M25, height: 107.5 mm, cable gland: without, Standard
Sleeve housing B48, for single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 5, straight, M25, height: 107.5 mm, cable gland: none, Standard

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |

## Additional Product Information

Technical dataProduct propertiesType B48
Product type Housing with locking latch
Application Standard
No. of cable outlets 5
Type of the screw connection M25
Housing type Sleeve housing
Cable outlet straight
Pg screw connection none
DimensionsDimensional drawing
Width 90 mm

Height 107.5 mm
Length 132 mm
Material specificationsHousing surface material uncoated
Impact strength IK08
Housing material Die-cast aluminum, salt water resistant
Mechanical propertiesMechanical data
Type of the screw connection M25
Locking type Pin
Environmental and real-life conditionsAmbient conditions
Degree of protection IP66
IP67
Enclosure rating (NEMA) 4 (UL 50e)
4X (UL 50e)
12 (UL 50e)
Impact strength IK08
Ambient temperature (operation) -40 °C ... 125 °C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-B48-HHFS-5TTM25-EM-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.