INDUSTRIAL COMPONENT DATA

HCS-C MINI 1 9V C C 7035 2203149 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-C MINI 1 9V C C 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-C MINI 1 9V C C 7035
Catalog number	2203149
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-3F1AAF2DE6
Generated	2026-11-18

Product Overview

Electronic housing
C-Mini portable case in light grey, consisting of two halves, screws. Front with 1.1 mm reinforcement, closed, battery compartment cover and battery contacts for 9 V block

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203149
Packing unit 1 pc
GTIN 4055626377025
Weight per Piece (excluding packing) 104.900 g
Custom tariff number 39269097
Country of origin DE (Germany)
Item properties
Type HCS-C MINI 1 9V C C 7035
Order No. 2203149
Housing type Handheld housing
Type straight
Battery compartment 9 V

Measurements
Dimensional drawing
Caption Schematic representation - for additional information, see product range drawing in the Download Center
Width [w] 70.5 mm
Height [h] 110 mm
Depth [d] 26 mm
Dimensions 60.5 mm x 100 mm x 1.1 mm (Recessed area on front)
Material specifications
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material ABS
Hammer test
Specification IEC 60068-2-75:2014-09
Impact energy 0.7 J
Number of drop cycles 5
Thermostability (ball thrust test)
Specification IEC 60695-10-2:2014-02
Temperature 80 °C
Test duration 1 h
Force 20
Test for assessing the risk of fire (glow wire)
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Degrees of protection provided by enclosures (IP code)
Specification IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
Result, degree of protection, IP code IP54
Packaging information
Pieces per package 1
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Classifications
eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 5.0EC001031ETIM 6.0EC001031
UNSPSC 6.0130211810UNS...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-C MINI 1 9V C C 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.