INDUSTRIAL COMPONENT DATA

HCS-C MINI 1W 3AAA 1 1 7035 2203152 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-C MINI 1W 3AAA 1 1 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-C MINI 1W 3AAA 1 1 7035
Catalog number	2203152
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-290C99AA74
Generated	2026-11-19

Product Overview

Electronic housing
C-Mini portable case in light gray, formed by two halves, two screens on the front side, screws. Front with 1.1 mm reinforcement, with window and keyboard slot, battery compartment cover and battery contacts for 3 AA batteries

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203152
Packing unit 1 pc
GTIN 4055626377056
Weight per Piece (excluding packing) 99.300 g
Custom tariff number 39269097
Country of origin DE (Germany)
Item properties
Type HCS-C MINI 1W 3AAA 1 1 7035
Order No. 2203152
Housing type Handheld housing
Type straight
Battery compartment 3 x AAA

Measurements
Dimensional drawing
Caption Schematic representation - for additional information, see product range drawing in the Download Center
Width [w] 70.5 mm
Height [h] 110 mm
Depth [d] 26 mm
Diagonal 2.8 in. (Window for display)
Dimensions 60.5 mm x 56 mm x 1.1 mm (Recessed area on front)
44 mm x 23.4 mm (Window for display)
Front with faceplate top, 1 x (49.8 mm x 17.8 mm)
bottom, 1 x (49.8 mm x 17.8 mm)
Material specifications
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material ABS
Hammer test
Specification IEC 60068-2-75:2014-09
Impact energy 0.7 J
Number of drop cycles 5
Thermostability (ball thrust test)
Specification IEC 60695-10-2:2014-02
Temperature 80 °C
Test duration 1 h
Force 20
Test for assessing the risk of fire (glow wire)
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Packaging information
Pieces per package 1
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Classifications
eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 5.0EC001031ETIM 6.0EC001031
UNSPSC 6.0130211810UNS...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-C MINI 1W 3AAA 1 1 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.