INDUSTRIAL COMPONENT DATA

# HCS-T MICRO C C C C 7035 2203124 PHOENIX CONTACT Electronic housing

**Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-T MICRO C C C C 7035**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | HCS-T MICRO C C C C 7035 |
| Catalog number | 2203124 |
| Category | Electronic enclosure |
| Minimum order | 1 Pcs |
| Document ID | EO-26C9E04A7E |
| Generated | 2026-11-19 |

## Product Overview

Electronic housing
T-Micro portable case in light grey, consisting of two halves with screws, smooth front, closed

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Key Commercial Data
Orderkey 2203124
Packing unit 1 pc
GTIN 4055626376820
Weight per Piece (excluding packing) 99.400 g
Custom tariff number 39269097
Country of origin DE (Germany)
Item properties
Type HCS-T MICRO C C C C 7035
Order No. 2203124
Housing type Handheld housing
Type straight
Battery compartment no
Measurements

Dimensional drawing
Caption Schematic representation - for additional information, see product range drawing in the Download Center
Width [ w ] 48 mm
Height [ h ] 150 mm
Depth [ d ] 28 mm
Material specifications
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material ABS
Hammer test
Specification IEC 60068-2-75:2014-09
Impact energy 0.7 J
Number of drop cycles 5
Thermostability (ball thrust test)
Specification IEC 60695-10-2:2014-02
Temperature 80 °C
Test duration 1 h
Force 20
Test for assessing the risk of fire (glow wire)
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Degrees of protection provided by enclosures (IP code)
Specification IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
Result, degree of protection, IP code IP54
Packaging information
Pieces per package 1
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Classifications
eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 5.0EC001031ETIM 6.0EC001031
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 13.239121409

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-T MICRO C C C C 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.