INDUSTRIAL COMPONENT DATA

HCS-T MICRO X 2AA C C 7035 2203127 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-T MICRO X 2AA C C 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-T MICRO X 2AA C C 7035
Catalog number	2203127
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-DA0B1CB3C9
Generated	2026-11-19

Product Overview

Electronic housing
T-Micro portable housing in light grey, consisting of two halves, screws, front with 1.1 mm reinforcement, closed with keyboard slot, cover for battery compartment and battery contacts, for 2 AA batteries

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203127
Packing unit 1 pc
GTIN 4055626376851
Weight per Piece (excluding packing) 105.500 g
Custom tariff number 39269097
Country of origin DE (Germany)
Item properties
Type HCS-T MICRO X 2AA C C 7035
Order No. 2203127
Housing type Handheld housing
Type straight
Max. IP code to attain IP40

Battery compartment 2 x AA
Measurements
Dimensional drawing
Caption Schematic representation - for additional information, see product range drawing in the Download Center
Width [w] 48 mm
Height [h] 150 mm
Depth [d] 28 mm
Dimensions 38 mm x 140 mm x 1.1 mm (Recessed area on front)
Material specifications
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material ABS
Hammer test
Specification IEC 60068-2-75:2014-09
Impact energy 0.7 J
Number of drop cycles 5
Thermostability (ball thrust test)
Specification IEC 60695-10-2:2014-02
Temperature 80 °C
Test duration 1 h
Force 20
Test for assessing the risk of fire (glow wire)
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Degrees of protection provided by enclosures (IP code)
Specification IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
Result, degree of protection, IP code IP40
Packaging information
Pieces per package 1
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Classifications
eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 5.0EC001031ETIM 6.0EC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-T MICRO X 2AA C C 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.