
INDUSTRIAL COMPONENT DATA

HDFKV 50-VP GNYE 0708797 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: HDFKV 50-VP GNYE



Manufacturer	PHOENIX CONTACT
MPN / Reference	HDFKV 50-VP GNYE
Catalog number	0708797
Category	Panel feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-44AF2DAC56
Generated	2026-11-18

Product Overview

Panel feed-through terminal block
Wall terminal block, connection type: Screw connection with traction capsule, Terminal connection, number of poles: 1, charging current: 150 A, cross-section: 16 mm² - 50 mm², conductor connection direction with respect to the plug direction: -90 °, width: 18.8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 0708797
Packing unit 10 pc
Minimum order quantity 10 pc
GTIN 4017918004767
Weight per Piece (excluding packing) 99.040 g
Custom tariff number 85369010
Country of origin GR (Greece)
General
Number of levels 1
Number of connections 2
Nominal cross section 50 mm²

Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Nominal current IN 150 A
Maximum load current 150 A
Nominal voltage UN 690 V
Number of positions 1
Dimensions
Width 18.8 mm
Pitch 18.8 mm
Connection data
Note Terminal sleeve
Connection side Level 1 ext. 1
Connection method Screw connection
Note Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.
Conductor cross section solid min. 16 mm²
Conductor cross section solid max. 50 mm²
Conductor cross section flexible min. 16 mm²
Conductor cross section flexible max. 50 mm²
Conductor cross section AWG min. 6
Conductor cross section AWG max. 1/0
Conductor cross section flexible, with ferrule without plastic sleeve min. 10 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 50 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 10 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 50 mm²
2 conductors with same cross section, solid min. 6 mm²
2 conductors with same cross se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HDFKV 50-VP GNYE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.