INDUSTRIAL COMPONENT DATA

# MC 0,5/ 8-G-2,54 SMD R44 1821753 PHOENIX CONTACT Printed-circuit board connector

**Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 0,5/ 8-G-2,54 SMD R44**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | MC 0,5/ 8-G-2,54 SMD R44 |
| Catalog number | 1821753 |
| Category | Printed circuit board connector |
| Minimum order | 465 Pcs |
| Document ID | EO-FEA5F6714D |
| Generated | 2026-11-18 |

## Product Overview

Printed-circuit board connector
Printed circuit board base housing, nominal section: 0.5 mm², color: black, nominal current: 6 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: MC 0.5/.. -G-SMD, pitch: 2.54 mm, mounting: SMD soldering, pin arrangement: Linear pin arrangement, number of solder pins per potential: 1, plug-in system: COMBICON FMC 0.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: 44 mm wide strap, Sample quantities available under SAMPLE MC...

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 1821753
Packing unit 465 pc
Minimum order quantity 465 pc
Note Made to Order (non-returnable)
Catalog page Page 177 (C-1-2013)
GTIN 4046356789912
Weight per Piece (excluding packing) 2.220 g
Custom tariff number 85366930

Country of origin PL (Poland)
Dimensions
Length [ l ] 7.1 mm
Width 24.9 mm
Pitch 2.54 mm
Dimension a 17.78 mm
Width [ w ] 24.9 mm
Height [ h ] 4.85 mm
Height 4.85 mm
Pin dimensions 0.64 x 0.64 mm
Length 7.1 mm
General
Range of articles MC 0,5/..-G-SMD
Insulating material group IIIa
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 32 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 6 A
Insulating material LCP
Flammability rating according to UL 94 V0
Color black
Number of positions 8
Standards and Regulations
Connection in acc. with standard EN-VDE
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 0,5/ 8-G-2,54 SMD R44 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.