
INDUSTRIAL COMPONENT DATA

MCV 0,5/16-G-2,54 SMDR72C1 1706094 PHOENIX CONTACT ?? ?? ?? ???

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 0,5/16-G-2,54 SMDR72C1



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 0,5/16-G-2,54 SMDR72C1
Catalog number	1706094
Category	Printed circuit board connector
Minimum order	315 Pcs
Document ID	EO-B46D7C38D1
Generated	2026-11-19

Product Overview

?? ?? ?? ???

Printed circuit board base housing, nominal section: 0.5 mm², color: black, nominal current: 6 A, dimensioning voltage (III/2): 160 V, contact surface: Gold, contact type: Male, Number of potentials: 16, Number of rows: 1, Number of poles per row: 16, number of connections: 16, family of articles: MCV 0.5/.. -G-SMD, pitch: 2.54 mm, mounting: SMD soldering, pin arrangement: Linear pad geometry, pin length [P]: 2 mm, Stecksystem: MICRO COMBICON - FMC 0.5, Lock: without, packaging type: 72 mm wide strap, Fixed first pole coding, can be combined with FMC 0.5/...-ST-2.54 C1 connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1706094
Packing unit 315 pc
Minimum order quantity 315 pc
Note Made to Order (non-returnable)
Catalog page Page 179 (C-1-2013)
GTIN 4046356842440
Weight per Piece (excluding packing) 2.220 g
Custom tariff number 85366930
Country of origin PL (Poland)

Dimensions
Length [l] 4.85 mm
Width 45.22 mm
Pitch 2.54 mm
Dimension a 38.1 mm
Width [w] 45.22 mm
Height [h] 7.1 mm
Height 7.1 mm
Length of the solder pin 2 mm
Pin dimensions 0.64 x 0.64 mm
Length 4.85 mm
General
Range of articles MCV 0,5/..-G-SMD
Insulating material group IIIa
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 32 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 6 A
Insulating material LCP
Flammability rating according to UL 94 V0
Color black
Number of positions 16
Standards and Regulations
Connection in acc. with standard EN-VDE
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 0,5/16-G-2,54 SMDR72C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.