
INDUSTRIAL COMPONENT DATA

MCV 1,5/ 3-GF-3,5 P20 THRR56 1780684 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 3-GF-3,5 P20 THRR56



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 3-GF-3,5 P20 THRR56
Catalog number	1780684
Category	Printed circuit board connector
Minimum order	200 Pcs
Document ID	EO-27E95EE178
Generated	2026-11-18

Product Overview

Printed-circuit board connector
Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MCV 1.5/.. -GF-THR, pitch: 3.5 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: Screw lock, fixing type: Air clamping (thread), packaging type: 56 mm wide strap, Further user information and design recommendations for Through Hole Reflow technology can be found at: Downloads

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1780684
Packing unit 200 pc
Minimum order quantity 200 pc
Note Made to Order (non-returnable)
Catalog page Page 211 (C-1-2013)
GTIN 4046356543989
Weight per Piece (excluding packing) 4.460 g
Custom tariff number 85366930

Country of origin DE (Germany)
Dimensions
Length [l] 6.9 mm
Width 20.8 mm
Pitch 3.5 mm
Dimension a 7 mm
Width [w] 20.8 mm
Height [h] 11.2 mm
Height 9.2 mm
Length of the solder pin 2 mm
Pin dimensions 0.8 x 0.8 mm
Length 6.9 mm
General
Range of articles MCV 1,5/..-GF-THR
Insulating material group IIIa
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 160 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Maximum load current 8 A
Insulating material LCP
Flammability rating according to UL 94 V0
Color black
Number of positions 3
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 3-GF-3,5 P20 THRR56 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.