INDUSTRIAL COMPONENT DATA

CCVA 2,5/ 2-G-5,08 RNP26THR 1956085 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: CCVA 2,5/ 2-G-5,08 RNP26THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	CCVA 2,5/ 2-G-5,08 RNP26THR
Catalog number	1956085
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-921B33A3A6
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: CCVA 2.5/.. -G-RN, pitch: 5.08 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: Locking by snap-on, fixing type: Snap-on protrusion, packing type: boxed packed, Snap-in flange item; for user information and design recommendations on Through Hole Reflow technology, see "Downloads"

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1956085
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 301 (C-1-2013)
GTIN 4017918926830
Weight per Piece (excluding packing) 0.910 g
Custom tariff number 85366930

Country of origin DE (Germany)
Dimensions
Length [l] 8.6 mm
Width 15.98 mm
Pitch 5.08 mm
Dimension a 5.08 mm
Width [w] 15.98 mm
Height [h] 14.6 mm
Height 12 mm
Length of the solder pin 2.6 mm
Pin dimensions 1 x 1 mm
Length 8.6 mm
General
Range of articles CCVA 2,5/..-G-RN
Insulating material group IIIa
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 400 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Maximum load current 12 A (per position)
Insulating material LCP
Flammability rating according to UL 94 V0
Color black
Number of positions 2
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CCVA 2,5/ 2-G-5,08 RNP26THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.