
INDUSTRIAL COMPONENT DATA

DFK-IPC 16/ 2-GFU-10,16 1702811 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-IPC 16/ 2-GFU-10,16



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-IPC 16/ 2-GFU-10,16
Catalog number	1702811
Category	Printed circuit board connector
Minimum order	10 Pcs
Document ID	EO-0C77883330
Generated	2026-11-18

Product Overview

Feed-through header
Wall pass-through housing, nominal section: 16 mm², color: green, nominal current: 76 A, dimensioning voltage (III/2): 1000 V, contact surface: silver, contact type: Female connection, Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, number of connections: 2, family of articles: DFK-IPC 16/.. -GFU, pitch: 10.16 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 4.1 mm, Stecksystem: POWER COMBICON 16, Locking: Screw locking, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1702811
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 579 (C-1-2013)
GTIN 4046356031400
Weight per Piece (excluding packing) 10.350 g
Custom tariff number 85366990
Country of origin PL (Poland)

Dimensions
Length [l] 34.55 mm
Width 61.4 mm
Pitch 10.16 mm
Dimension a 10.16 mm
Width [w] 61.4 mm
Height [h] 22 mm
Height 19.9 mm
Length of the solder pin 4.1 mm
Pin dimensions 0.8 x 1.2 mm
Pin spacing 10.16 mm
Length 34.55 mm
General
Range of articles DFK-IPC 16/..-GFU
Insulating material group I
Rated surge voltage (III/3) 8 kV
Rated surge voltage (III/2) 8 kV
Rated surge voltage (II/2) 6 kV
Rated voltage (III/3) 1000 V
Rated voltage (III/2) 1000 V
Rated voltage (II/2) 1000 V
Connection in acc. with standard EN-VDE
Nominal current IN 76 A
Maximum load current 76 A
Insulating material PA
Flammability rating according to UL 94 V0
Color green
Number of positions 2
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC001283ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 113912140...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-IPC 16/ 2-GFU-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.