
INDUSTRIAL COMPONENT DATA

DFK-PC 5/ 8-G-7,62 1727647 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-PC 5/ 8-G-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-PC 5/ 8-G-7,62
Catalog number	1727647
Category	Printed circuit board connector
Minimum order	10 Pcs
Document ID	EO-2225AAF50D
Generated	2026-11-18

Product Overview

Printed-circuit board connector
Wall pass-through housing, nominal section: 6 mm², color: green, nominal current: 41 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: DFK-PC 5/.. -G, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4.9 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed
Through socket, nominal cross-section: 6 mm2, colour: green, nominal current: 41 A, reference voltage (III/2): 630 V, contact area: Sn, contact type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, item range: DFK-PC 5/.. -G, pitch: 7.62 mm, mounting: Wave welding, spindle plane: Linear broaching, spindle length [P]: 4.9 mm, number of pins per potential: 3, Plug-in system: COMBICON PC 5, Orientation of the plug-in pattern: Standard, locking: without, fastening type: without, packaging type: packed in a carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1727647
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)

Catalog page Page 544 (C-1-2013)
GTIN 4046356135795
Weight per Piece (excluding packing) 23.850 g
Custom tariff number 85366990
Country of origin PL (Poland)
Dimensions
Length [l] 41.65 mm
Width 86.46 mm
Pitch 7.62 mm
Dimension a 53.34 mm
Width [w] 86.46 mm
Height [h] 21.1 mm
Height 19.54 mm
Length of the solder pin 4.9 mm
Pin dimensions 1 x 0.8 mm
Pin spacing 7.62 mm
Length 41.65 mm
General
Range of articles DFK-PC 5/..-G
Insulating material group I
Rated surge voltage (III/3) 6 kV
Rated surge voltage (III/2) 6 kV
Rated surge voltage (II/2) 6 kV
Rated voltage (III/3) 500 V
Rated voltage (III/2) 630 V
Rated voltage (II/2) 800 V
Connection in acc. with standard EN-VDE
Nominal current IN 41 A
Maximum load current 41 A
Insulating material PA
Flammability rating according to UL 94 V0
Color green
Number of positions 8
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPS...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-PC 5/ 8-G-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.