INDUSTRIAL COMPONENT DATA

# IPC 16/ 9-G-10,16 1969603 PHOENIX CONTACT Feed-through header

**Brand: PHOENIX CONTACT | Manufacturer Part Number: IPC 16/ 9-G-10,16**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | IPC 16/ 9-G-10,16 |
| Catalog number | 1969603 |
| Category | Printed circuit board connector |
| Minimum order | 50 Pcs |
| Document ID | EO-B495B2CB89 |
| Generated | 2026-11-19 |

## Product Overview

Feed-through header
Printed circuit board base housing, nominal section: 16 mm², color: green, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Female, number of potentials: 9, number of rows: 1, number of poles: 9, number of connections: 9, article family: IPC 16/.. -G, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 1969603
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 570 (C-1-2013)
GTIN 4017918943844
Weight per Piece (excluding packing) 31.560 g
Custom tariff number 85366930
Country of origin PL (Poland)

Dimensions
Length [ l ] 32.1 mm
Width 92.24 mm
Pitch 10.16 mm
Dimension a 81.28 mm
Width [ w ] 92.24 mm
Height [ h ] 17.6 mm
Height 13.6 mm
Length of the solder pin 4 mm
Pin dimensions 0.8 x 1.2 mm
Pin spacing 10.16 mm
Length 32.1 mm
General
Range of articles IPC 16/..-G
Insulating material group I
Rated surge voltage (III/3) 8 kV
Rated surge voltage (III/2) 8 kV
Rated surge voltage (II/2) 8 kV
Rated voltage (III/3) 1000 V
Rated voltage (III/2) 1000 V
Rated voltage (II/2) 1000 V
Nominal current IN 76 A
Maximum load current 76 A
Insulating material PA
Flammability rating according to UL 94 V0
Color green
Number of positions 9
Standards and Regulations
Connection in acc. with standard CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IPC 16/ 9-G-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.