
INDUSTRIAL COMPONENT DATA

MC 1,5/ 7-GF-3,81 P26 THRR56 1781968 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 7-GF-3,81 P26 THRR56



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 7-GF-3,81 P26 THRR56
Catalog number	1781968
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-0DFA0A7038
Generated	2026-11-18

Product Overview

MC 1,5/ 7-GF-3,81 P26 THRR56 1781968 PHOENIX CONTACT Printed-circuit board connector

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	**Fixed connector**
Contact type (EF001587)	**Pin**
Number of plug-in contact rows (EF006935)	**1**
Modular spacing contacts (EF007326)	**3.81 mm**
Modular spacing connections (EF006827)	**3.81 mm**
Rated current In (EF008250)	**8 A**
Rated voltage (EF000228)	**160 V**
Rated surge voltage (EF002993)	**2.5 kV**
Over voltage category (EF006785)	**III**
Pollution degree (EF006786)	**2**
Material of contact surface (EF004020)	**Tin**
Type of electric connection (EF003961)	**Other**
Diameter connection pin (EF006823)	**1.4 mm**
Length pin (EF006825)	**2.6 mm**
Material insulation body (EF007543)	**Other**

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Housing colour (EF000136)	**Black**
Inflammability class of insulation material according to UL94 (EF002521)	**V0**
Operating temperature (EF002393)	**-40 °C**
Type of fastening (EF002442)	**Other**
Type of banding (EF007011)	**Other**

Classification & Catalog Path

Catalog path	**PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Printed-circuit board connector
Printed circuit board base case, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 7, family of articles: MC 1.5/.. -GF-THR, pitch: 3.81 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: 56 mm wide strap

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 7-GF-3,81 P26 THRR56 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.