INDUSTRIAL COMPONENT DATA

# MCD 0,5/ 2-G1-2,5 1894804 PHOENIX CONTACT Feed-through header

**Brand: PHOENIX CONTACT | Manufacturer Part Number: MCD 0,5/ 2-G1-2,5**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | MCD 0,5/ 2-G1-2,5 |
| Catalog number | 1894804 |
| Category | Printed circuit board connector |
| Minimum order | 50 Pcs |
| Document ID | EO-863F517887 |
| Generated | 2026-11-19 |

## Product Overview

Feed-through header
Printed circuit board base housing, nominal section: 0.5 mm², color: green, nominal current: 4 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 2, number of poles: 2, number of connections: 4, family of articles: MCD 0.5/.. -G1, pitch: 2.5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.8 mm, number of soldering pins per potential: 1, plug-in system: COMBICON FK-MC 0.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 1894804
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 173 (C-1-2013)
GTIN 4017918162078
Weight per Piece (excluding packing) 2.330 g
Custom tariff number 85366930
Country of origin PL (Poland)
Dimensions

Length [ l ] 17.5 mm
Width 6.9 mm
Pitch 2.5 mm
Dimension a 2.5 mm
Width [ w ] 6.9 mm
Height [ h ] 25.65 mm
Height 21.85 mm
Length of the solder pin 3.8 mm
Pin dimensions 0.8 x 0.8 mm
Pin spacing 2.50 mm
Length 17.5 mm
General
Range of articles MCD 0,5/..-G1
Insulating material group I
Rated surge voltage (III/3) 1.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 80 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 4 A
Maximum load current 4 A
Insulating material PA
Flammability rating according to UL 94 V0
Color green
Number of positions 2
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCD 0,5/ 2-G1-2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.