INDUSTRIAL COMPONENT DATA

MCDV 1,5/ 2-GF-3,81 1830253 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDV 1,5/ 2-GF-3,81



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDV 1,5/ 2-GF-3,81
Catalog number	1830253
Category	Printed circuit board connector
Minimum order	80 Pcs
Document ID	EO-23B2D54F4A
Generated	2026-11-19

Product Overview

Feed-through header
Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 2, number of poles: 2, number of connections: 4, family of articles: MCDV 1.5/.. -GF, pitch: 3.81 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed packaging, In the case of a combination with MCV plug-in parts, an MCVW connector and an MCVR connector must be used, respectively. PCB base socket, nominal cross-section: 1.5 mm2, colour: green, rated current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Sn, contact connection type: plug, number of potentials: 4, number of rows: 2, number of poles: 2, number of connections: 4, product series: MCDV 1.5/...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1830253
Packing unit 50 pc
Catalog page Page 237 (C-1-2013)
GTIN 4017918110826
Weight per Piece (excluding packing) 4.100 g

Custom tariff number 85366930
Country of origin DE (Germany)
Dimensions
Length [l] 22.7 mm
Width 18.01 mm
Pitch 3.81 mm
Dimension a 3.81 mm
Width [w] 18.01 mm
Height [h] 25.3 mm
Height 21.9 mm
Length of the solder pin 3.4 mm
Pin dimensions 0.8 x 0.8 mm
Pin spacing 15.24 mm
Length 22.7 mm
General
Range of articles MCDV 1,5/..-GF
Insulating material group I
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 160 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Maximum load current 8 A
Insulating material PA
Flammability rating according to UL 94 V0
Color green
Number of positions 2
Standards and Regulations
Connection in acc. with standard EN-VDE
CSA
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDV 1,5/ 2-GF-3,81 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.