
INDUSTRIAL COMPONENT DATA

MCV 1,5/12-G-3,81 P26 THRR72 1712982 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/12-G-3,81 P26 THRR72



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/12-G-3,81 P26 THRR72
Catalog number	1712982
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-98760860B7
Generated	2026-11-19

Product Overview

MCV 1,5/12-G-3,81 P26 THRR72 1712982 PHOENIX CONTACT Feed-through header

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	**Fixed connector**
Contact type (EF001587)	**Pin**
Number of poles (EF001391)	**12**
Number of plug-in contact rows (EF006935)	**1**
Modular spacing contacts (EF007326)	**3.81 mm**
Modular spacing connections (EF006827)	**3.81 mm**
Rated current In (EF008250)	**8 A**
Rated voltage (EF000228)	**160 V**
Rated surge voltage (EF002993)	**2.5 kV**
Over voltage category (EF006785)	**III**
Pollution degree (EF006786)	**2**
Material of contact surface (EF004020)	**Tin**
Type of electric connection (EF003961)	**Other**
Diameter connection pin (EF006823)	**1.4 mm**
Length pin (EF006825)	**2.6 mm**

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Material insulation body (EF007543)	**Other**
Housing colour (EF000136)	**Black**
Inflammability class of insulation material according to UL94 (EF002521)	**V0**
Operating temperature (EF002393)	**-40 °C**
Type of fastening (EF002442)	**Other**
Type of banding (EF007011)	**Other**

Classification & Catalog Path

Catalog path	**PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Feed-through header
Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, article family: MCV 1.5/.. -G-THR, pitch: 3.81 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 72 mm wide strap

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/12-G-3,81 P26 THRR72 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.