
INDUSTRIAL COMPONENT DATA

PC 6-16/ 2-G1U-10,16 1996236 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 6-16/ 2-G1U-10,16



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 6-16/ 2-G1U-10,16
Catalog number	1996236
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-2A125176D1
Generated	2026-11-18

Product Overview

Feed-through header
Printed circuit board base housing, nominal section: 16 mm², color: green, nominal current: 76 A (41 A in combination with PC 6 connector), nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: PC 6-16/.. -G1U, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: inverted, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1996236
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 567 (C-1-2013)
GTIN 4046356037976
Weight per Piece (excluding packing) 8.250 g
Custom tariff number 85366930

Country of origin PL (Poland)
Item properties
Brief article description Feed-through header
Plug-in system POWER COMBICON 16
Type of contact Male connector
Range of articles PC 6-16/..-G1U
Pitch 10.16 mm
Number of positions 2
Mounting type Wave soldering
Pin layout Linear pinning
Locking without
Number of levels 1
Number of connections 2
Number of potentials 2
Electrical parameters
Rated current 76 A (41 A in combination with PC 6 plug)
Rated insulation voltage (III/2) 1000 V
Rated surge voltage (III/2) 8 kV
Material data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Electroplated silver
Metal surface contact area (top layer) Silver (4 - 8 µm Ag)
Metal surface contact area (middle layer) Nickel (2 - 4 µm Ni),
Metal surface soldering area (top layer) Silver (4 - 8 µm Ag)
Metal surface soldering area (middle layer) Nickel (2 - 4 µm Ni)
Material data - housing
Insulating material PA
Insulating material group I
CTI according to IEC 60112 600
Flammability rating according to UL 94 V0
Glow wire flammability index GWFI according to EN 60695-2-12 850
Glow wire ignition temperature GWIT according to EN 60695-2-13 775
Temperature for the ball....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 6-16/ 2-G1U-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.