INDUSTRIAL COMPONENT DATA

PST 1,0/ 5-H-3,5 1737048 PHOENIX CONTACT Pin strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: PST 1,0/ 5-H-3,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	PST 1,0/ 5-H-3,5
Catalog number	1737048
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-6708C5BC7C
Generated	2026-11-19

Product Overview

Pin strip
Male connector, nominal section: 1.5 mm², color: black, nominal current: 8 A (Depending on the connector used), nominal voltage (III/2): 250 V, contact surface: Tin, contact type: Male, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, article family: PST 1.0/.. -H, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 6.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON PST 1.0, locking: without, fixing type: without, packaging type: boxed, The maximum current depends on the connector used. Of the two current values, the lower value for the connector and the male connector is decisive. The plug is made of high-temperature resistant plastic, making it suitable for the reflow soldering process.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1737048
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 433 (C-1-2013)
GTIN 4046356183451
Weight per Piece (excluding packing) 0.730 g
Custom tariff number 85366930

Country of origin SK (Slovakia)
Dimensions
Length [l] 10.5 mm
Width 17.5 mm
Pitch 3.5 mm
Dimension a 14 mm
Width [w] 17.5 mm
Height [h] 9.4 mm
Height 2.8 mm
Length of the solder pin 6.6 mm
Pin dimensions ø 1 mm
Length 10.5 mm
General
Range of articles PST 1,0/..-H
Insulating material group IIIa
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 160 V
Rated voltage (III/2) 250 V
Rated voltage (II/2) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A (depends on the plug used)
Maximum load current 8 A (depends on the plug used)
Insulating material PA
Flammability rating according to UL 94 V0
Color black
Number of positions 5
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211801UNSPSC 7.09013912...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PST 1,0/ 5-H-3,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.