INDUSTRIAL COMPONENT DATA

# PTSM 0,5/ 6-HH-2,5-SMD R44 1778803 PHOENIX CONTACT Feed-through header

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PTSM 0,5/ 6-HH-2,5-SMD R44**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PTSM 0,5/ 6-HH-2,5-SMD R44 |
| Catalog number | 1778803 |
| Category | Printed circuit board connector |
| Minimum order | 1 Pcs |
| Document ID | EO-9320DD6F30 |
| Generated | 2026-11-18 |

## Product Overview

PTSM 0,5/ 6-HH-2,5-SMD R44 1778803 PHOENIX CONTACT Feed-through header

STRUCTURED PRODUCT DATA

## Technical Specifications

| TECHNICAL ATTRIBUTE | VALUE |
|---|---|
| Connector model (EF007495) | **Fixed connector** |
| Contact type (EF001587) | **Pin** |
| Number of poles (EF001391) | **6** |
| Number of plug-in contact rows (EF006935) | **1** |
| Modular spacing contacts (EF007326) | **2.5 mm** |
| Modular spacing connections (EF006827) | **2.5 mm** |
| Rated current In (EF008250) | **6 A** |
| Rated voltage (EF000228) | **160 V** |
| Rated surge voltage (EF002993) | **2.5 kV** |
| Over voltage category (EF006785) | **III** |
| Pollution degree (EF006786) | **2** |
| Material of contact surface (EF004020) | **Tin** |
| Type of electric connection (EF003961) | **Other** |
| Material insulation body (EF007543) | **Other** |
| Housing colour (EF000136) | **Black** |

CONTINUED

## Technical Specifications

| TECHNICAL ATTRIBUTE | VALUE |
|---|---|
| **Inflammability class of insulation material according to UL94 (EF002521)** | **V0** |
| Operating temperature (EF002393) | **-40 °C** |
| Type of fastening (EF002442) | **Other** |
| Type of banding (EF007011) | **Other** |

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | **PHOENIX CONTACT > PCB Connectors (PCC)** |

## Additional Product Information

Feed-through header
Printed circuit board base case, nominal section: 0.5 mm², color: black, nominal current: 6 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, article family: PTSM 0.5/.. -HH-SMD, pitch: 2.5 mm, mounting: SMD soldering, pin arrangement: Linear pin arrangement, number of solder pins per potential: 1, plug-in system: COMBICON PTSM, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 44 mm wide strap, Item with twist protection pins

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTSM 0,5/ 6-HH-2,5-SMD R44 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.