
INDUSTRIAL COMPONENT DATA

SMC 1,5/11-GF-3,81 1827512 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMC 1,5/11-GF-3,81



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMC 1,5/11-GF-3,81
Catalog number	1827512
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-8533168515
Generated	2026-11-18

Product Overview

Feed-through header
Printed circuit board base case, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 11, number of rows: 1, number of poles: 11, number of connections: 11, family of articles: SMC 1.5/.. -GF, pitch: 3.81 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1827512
Packing unit 50 pc
Note Made to Order (non-returnable)
Catalog page Page 229 (C-1-2013)
GTIN 4017918114619
Weight per Piece (excluding packing) 3.860 g
Custom tariff number 85366930
Country of origin DE (Germany)
Dimensions

Length [l] 13.11 mm
Width 52.3 mm
Pitch 3.81 mm
Dimension a 38.1 mm
Width [w] 52.3 mm
Height [h] 14.42 mm
Height 11.02 mm
Length of the solder pin 3.4 mm
Pin dimensions 0.8 x 0.8 mm
Length 13.11 mm
General
Range of articles SMC 1,5/..-GF
Insulating material group I
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 160 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Maximum load current 8 A
Insulating material PA
Flammability rating according to UL 94 V0
Color green
Number of positions 11
Standards and Regulations
Connection in acc. with standard EN-VDE
CSA
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMC 1,5/11-GF-3,81 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.