INDUSTRIAL COMPONENT DATA

HC-EVO-B16-BFDC-PLRBK 1407649 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-EVO-B16-BFDC-PLRBK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-EVO-B16-BFDC-PLRBK
Catalog number	1407649
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-4C7251121B
Generated	2026-11-18

Product Overview

Housing
HEAVYCON EVO recessed housing, plastic, B16, for transverse locking, height 30.5 mm, with flat joint, with protective cover

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1407649
Packing unit 1 pc
Catalog page Page 616 (C-2-2017)
GTIN 4046356777124
Weight per Piece (excluding packing) 103.800 g
Custom tariff number 85389099
Country of origin PL (Poland)
Dimensions
Height 30.5 mm
Width 53 mm
Length 114 mm
Length of the assembly cutout 86 mm

Width of the assembly cutout 35 mm
Ambient conditions
Degree of protection (IP) IP66 (when plugged in)
IP54 (with closed protective cover)
Degree of protection (NEMA) 12 (UL 50e)
Ambient temperature (operation) -40 °C ... 125 °C
General
Note For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K, HV06-I-PR, HV 6-E...C
Size B16
Housing type Panel mounting base
Color black
Locking type for double locking latch
Torque 0.5 Nm ... 1.7 Nm (Fixing screws for panel mounting base)
Screw connection none
Protective cover yes
Housing material PA
Seal material NBR
Material, protective cover PA
Flammability rating according to UL 94 V0
Assembly instructions Not for D series terminal adapters
Connection Not for HC-B 24-ADP-B..... adapter plates
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027143424eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202
ETIM 3.0EC000437ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437
UNSPSC 6.01...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-EVO-B16-BFDC-PLRBK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.