INDUSTRIAL COMPONENT DATA

HC-B 24-EBUQ-2,5-48 1605608 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 24-EBUQ-2,5-48



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 24-EBUQ-2,5-48
Catalog number	1605608
Category	Contact insert for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-B9D9ED05CE
Generated	2026-11-18

Product Overview

Contact insert
Contact insert, number of poles: 24+PE, size: B24, Female, QUICKON connection, 500 V, 16 A, 0.34 mm² ... 2.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1605608
Packing unit 10 pc
Note Made to Order (non-returnable)
Catalog page Page 541 (C-2-2017)
GTIN 4017918940690
Weight per Piece (excluding packing) 126.680 g
Custom tariff number 85366990
Country of origin PL (Poland)
General
Note For HEAVYCON-ADVANCE housing of B24 type and HEAVYCON housing of B24/B48 type. Encoding using coding profile CP-HC (1686478). HC-B6.../ HC-B10... for two coding profiles. HC-B16.../ HC-B24... for four coding profiles.
Connectors may only be actuated when there is no load/voltage.
Connectors may be operated only when there is no load/voltage.

Connection method QUICKON connection
Degree of pollution 3
Overvoltage category III
Number of positions 24+PE
Insertion/withdrawal cycles >= 500
Size B24
Contact numbering 1 - 24
Conductor cross section 0.34 mm² ... 2.5 mm² (Litz wire structure VDE 0295, Class 1 - 5/litz wire diameter >= 0.2 mm)
Connection cross section AWG 22 ... 14
Wire diameter including insulation 1 mm ... 3.5 mm
Frequency of connections between conductors of the same cross section 10
Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required
Connection For housings of type B16/B32. Connectors may only be actuated when there is no load/voltage.
Ambient conditions
Ambient temperature (operation) -40 °C ... 125 °C (including heating up of contacts)
Ambient temperature (assembly) -25 °C ... 50 °C
Material data
Contact material Copper alloy
Contact surface mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 24-EBUQ-2,5-48 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.