INDUSTRIAL COMPONENT DATA

HC-D 15-I-CT-F 1584389 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-D 15-I-CT-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-D 15-I-CT-F
Catalog number	1584389
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-7E116836E0
Generated	2026-11-19

Product Overview

Contact insert
Contact insert, number of poles: 15+PE, size: D15, number of connections per pole: 1, Female, Crimped connection, 250 V, 10 A, 0.14 mm² ... 2.5 mm²
Contact insert, number of positions: 15+PE, size: D15, number of connections per position: 1, Socket, Crimp connection, 250 V, 10 A, 0.14 mm2 ... 2.5 mm2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral For HC-D15 housing, crimp contacts CK1,6-ED (crimp contacts not included in scope of supply)
General Connectors may be operated only when there is no load/voltage.
General It is imperative that guide pins (HC-CST) and sockets (HC-CBU) are used to prevent tip collision due to misalignment.
MountingAssembly note To ensure correct use, installation in housing with IP54 protection or better is required
Product propertiesProduct type Contact insert with a fixed no. of positions
Series HC-D
Type D15
Number of positions 15
Note number of positions 15+PE
Connection profile 15+PE

Number of connections per position 1
Contact material type turned
rolled
Data management status
Article revision 08
Insulation characteristics
Overvoltage category III
Degree of pollution 3
DimensionsDimensional drawing
Width 22.5 mm
Height 33.5 mm
Length 55.4 mm
Drill hole distance, horizontal 49.5 mm
Drill hole distance, vertical 16 mm
Mechanical characteristics
Contact diameter 1.6 mm
Connection dataConnection technology
Connection technology Crimp connection
Number of connections per position 1
Connection in acc. with standard IEC / EN
Conductor connection
Conductor cross section 0.14 mm² ... 2.5 mm²
Connection cross section AWG 26 ... 14
Tightening torque 0.7 Nm ... 1 Nm (PE connection)
0.5 Nm ... 0.8 Nm (Mounting screws for mounting in the HEAVYCON housing)
Stripping length of the individual wire 8 mm (0.14 mm² ... 1.5 mm²)
6 mm (2.5 mm²)
Electrical propertiesRated voltage (I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-D 15-I-CT-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.