INDUSTRIAL COMPONENT DATA

HC-B 24-TFL-H-O1STM32S 1460213 PHOENIX CONTACT HEAVYCON B24 sleeve housing, for single locking latch, height..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 24-TFL-H-O1STM32S



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 24-TFL-H-O1STM32S
Catalog number	1460213
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-2E627D1381
Generated	2026-11-18

Product Overview

HEAVYCON B24 sleeve housing, for single locking latch, height: 76 mm, with 1 x M32 thread, lateral cable outlet
HEAVYCON B24 aerial housing, for longitudinal locking, height 76 mm, with 1 M32 thread, side cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Dimensions
Height 76 mm
Width 43 mm
Length 120 mm
Ambient conditions
Degree of protection of housing (IP) IP65
Ambient temperature (operation) -40 °C ... 125 °C
General
Note For contact inserts HC-B24, BB46, BBB64, D64, DD108, M
Type B24
Housing type Sleeve housing
Locking type for single locking latch

No. of cable outlets 1
Cable exit Lateral
Screw connection none
Type of the screw connection 1x M32
Housing material Aluminum die-cast
Housing surface material Powder-coated, gray

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 24-TFL-H-O1STM32S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.