INDUSTRIAL COMPONENT DATA

HC-B 24-TFQ-H-O1STM32S 1409367 PHOENIX CONTACT HEAVYCON B24 sleeve housing, for double locking latch, height..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 24-TFQ-H-O1STM32S



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 24-TFQ-H-O1STM32S
Catalog number	1409367
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-886946404D
Generated	2026-11-18

Product Overview

HEAVYCON B24 sleeve housing, for double locking latch, height: 76 mm, with 1 x M32 thread, lateral cable outlet
HEAVYCON B24 aerial housing, for cross flange, height 76 mm, with 1x M32 thread, side cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Dimensions
Height 76 mm
Width 43 mm
Length 120 mm
Ambient conditions
Degree of protection of housing (IP) IP65
Ambient temperature (operation) -40 °C ... 125 °C
General
Note For contact inserts HC-B24, BB46, BBB64, D64, DD108, M
Type B24
Housing type Sleeve housing
Locking type For double locking latch

No. of cable outlets 1
Cable exit Lateral
Screw connection none
Type of the screw connection 1x M32
Housing material Aluminum die-cast
Housing surface material Powder-coated, gray

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 24-TFQ-H-O1STM32S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.