
INDUSTRIAL COMPONENT DATA

HC-B 24-I-CT-M 1648335 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 24-I-CT-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 24-I-CT-M
Catalog number	1648335
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-FD0831378C
Generated	2026-11-19

Product Overview

Contact insert
Contact insert, number of poles: 24+PE, size: B24, number of connections per pole: 1, Male, Crimped connection, 500 V, 16 A, 0.5 mm² ... 4 mm², Application: Power
Contact insert, number of positions: 24+PE, size: B24, number of connections per position: 1, Pin, Crimp connection, 500 V, 16 A, 0.5 mm2 ... 4 mm2, application: Power

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral For HEAVYCON ADVANCE and HEAVYCON housing of B24 type, crimp contacts CK 2,5-ED (crimp contacts not included in the scope of supply).
General Connectors may be operated only when there is no load/voltage.
MountingAssembly note To ensure correct use, installation in housing with IP54 protection or better is required
Remove the crimp contact using a screwdriver. The opening for the screwdriver is next to the opening where the conductor is inserted.
Product propertiesProduct type Contact insert with a fixed no. of positions
Series HC-B
Application Power
Type B24
B48
Number of positions 24

Connection profile 24+PE
Contact numbering 1 - 24
Number of connections per position 1
Contact material type turned
Data management status
Article revision 11
Insulation characteristics
Overvoltage category III
Degree of pollution 3
DimensionsDimensional drawing
Width 34 mm
Height 32 mm
Length 111 mm
Drill hole distance, horizontal 104 mm
Mechanical characteristics
Contact diameter 2.5 mm
Connection dataConnection technology
Connection technology Crimp connection
Number of connections per position 1
Connection in acc. with standard IEC / EN
Conductor connection
Conductor cross section 0.5 mm² ... 4 mm²
Connection cross section AWG 20 ... 12
Tightening torque 0.8 Nm ... 1.2 Nm (PE connection)
0.5 Nm ... 0.8 Nm (Mounting screws for mounting in the HEAVYCON housing)
Stripping length of the individual wire 7.5 mm
Electrical propertiesRated voltage (III/3) 500 V
Rated sur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 24-I-CT-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.