INDUSTRIAL COMPONENT DATA

HC-DD108-I-CT-M-216 1584127 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-DD108-I-CT-M-216



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-DD108-I-CT-M-216
Catalog number	1584127
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-9196BFB463
Generated	2026-11-18

Product Overview

Contact insert
Contact insert, number of poles: 108+PE, size: B24, Male, Crimped connection, 250 V, 10 A, 0.14 mm² ... 2.5 mm², application: Signal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1584127
Packing unit 1 pc
Catalog page Page 533 (C-2-2017)
GTIN 4046356133432
Weight per Piece (excluding packing) 66.300 g
Custom tariff number 85389099
Country of origin CN (China)
General
Note For HEAVYCON ADVANCE and HEAVYCON housing of B24 type, crimp contacts CK 1,6-ED (crimp contacts not included in the scope of supply). Plug-in connections may only be operated only when there is no load/voltage.
Connection method Crimp connection
Degree of pollution 3

Overvoltage category III
Number of positions 108+PE
Insertion/withdrawal cycles >= 500
Size B24
Contact numbering 109 - 216
Conductor cross section 0.14 mm² ... 2.5 mm²
Connection cross section AWG 26 ... 14
Stripping length of the individual wire 8 mm (0.14 ... 1.5 mm²)
6 mm (2.5 mm²)
Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required
Connection Connectors may be plugged in only when there is no load/voltage.
Ambient conditions
Ambient temperature (operation) -40 °C ... 125 °C (including heating up of contacts)
Material data
Contact material Copper alloy
Contact surface material Ag (alternatively Au)
Contact carrier material PC
Standards/regulations PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
Electrical characteristics
Rated voltage (III/3) 250 V
Rated surge voltage 4 kV
Rated current 10 A
Standards and Regulations
Connection in acc. with standard CSA
Const...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-DD108-I-CT-M-216 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.