INDUSTRIAL COMPONENT DATA

# HC-D 25-I-CT-M-Z 1411478 PHOENIX CONTACT Contact insert

**Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-D 25-I-CT-M-Z**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | HC-D 25-I-CT-M-Z |
| Catalog number | 1411478 |
| Category | Contact insert for rectangular connectors |
| Minimum order | 1 Pcs |
| Document ID | EO-0639EB2122 |
| Generated | 2026-11-18 |

## Product Overview

Contact insert

Contact insert, number of poles: 25+PE, size: D25, Male, Crimped connection, 250 V, 10 A, 0.14 mm² ... 2.5 mm²

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |

## Additional Product Information

Key Commercial Data
Orderkey 1411478
Packing unit 1 pc
Catalog page Page 517 (C-2-2017)
GTIN 4046356921824
Weight per Piece (excluding packing) 31.500 g
Custom tariff number 85389099
Country of origin CN (China)
General
Note For HEAVYCON housing type D25, CK1,6-ED crimp contacts (crimp contacts not supplied as standard)
Connection method Crimp connection
Degree of pollution 3
Overvoltage category III
Number of positions 25+PE
Insertion/withdrawal cycles >= 500

Size D25
Conductor cross section 0.14 mm² ... 2.5 mm²
Connection cross section AWG 26 ... 14
Stripping length of the individual wire 8 mm
6 mm (2.5 mm²)
Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required
Connection Connectors may be plugged in only when there is no load/voltage.
Ambient conditions
Ambient temperature (operation) -40 °C ... 125 °C (including heating up of contacts)
Material data
Contact material Copper alloy
Contact surface material Ag (alternatively Au)
Contact carrier material PA
Electrical characteristics
Rated voltage (III/3) 250 V
Rated surge voltage 4 kV
Rated current 10 A
Standards and Regulations
Constructional and testing regulations DIN VDE 0627/86
DIN VDE 0110/02.79
DIN VDE 0110-1/04.97
IEC 60664-1, DIN IEC 60512
IEC 60352
Flammability rating according to UL 94 V0
Classifications
eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440205eCl@ss 8.027440205eCl@ss 9.027440205
ETIM 4.0EC002498ETIM 5.0EC000438ETIM 6.0EC000438
UNSPSC 13.239121...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-D 25-I-CT-M-Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.