INDUSTRIAL COMPONENT DATA

# PTPOWER 95-3L/N/FE 3260118 PHOENIX CONTACT High-current terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PTPOWER 95-3L/N/FE**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PTPOWER 95-3L/N/FE |
| Catalog number | 3260118 |
| Category | Feed-through terminal block |
| Minimum order | 2 Pcs |
| Document ID | EO-909ED01286 |
| Generated | 2026-11-18 |

## Product Overview

High-current terminal block
Current terminal, locked, rated voltage: 1000 V, rated current: 232 A, number of connections: 10, number of poles: 5, connection type: PowerTurn connection, 1st floor, cross-section: 25 mm² - 95 mm², mounting class: NS 35/15, color: gray/blue/black-yellow
High Current Terminal, Blocked, Nominal Voltage: 1000 V, Rated Current: 232 A, Number of Connections: 10, Number of Poles: 5, Connection Type: PowerTurn Connection, Cross Section: 25 mm2 - 95 mm2, Mounting Type: NS 35/15, Colour: grey/blue/black-yellow

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Key Commercial Data
Orderkey 3260118
Packing unit 2 pc
Minimum order quantity 2 pc
Note Made to Order (non-returnable)
Catalog page Page 129 (C-1-2017)
GTIN 4046356778985
Weight per Piece (excluding packing) 984.650 g
Custom tariff number 85369010

Country of origin PL (Poland)
General
Number of positions 5
Number of levels 1
Number of connections 10
Potentials 5
Nominal cross section 95 mm²
Color gray/blue/black-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 7.54 W
Maximum load current 232 A (with 95 mm2conductor cross section)
Nominal current IN 232 A
Nominal voltage UN 1000 V AC
1500 V DC
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protec...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTPOWER 95-3L/N/FE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.