
INDUSTRIAL COMPONENT DATA

PTPOWER 95 BU 3260103 PHOENIX CONTACT High-current terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTPOWER 95 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTPOWER 95 BU
Catalog number	3260103
Category	Feed-through terminal block
Minimum order	3 Pcs
Document ID	EO-B96C4B9965
Generated	2026-11-18

Product Overview

High-current terminal block
Current terminal, nominal voltage: 1000 V, nominal current: 232 A, number of connections: 2, number of poles: 1, connection type: PowerTurn connection, 1st floor, cross-section: 25 mm² - 95 mm², mounting class: NS 35/15, color: blue
High-current terminal block, nom. voltage: 1000 V, nominal current: 232 A, number of connections: 2, number of positions: 1, connection method: PowerTurn connection, cross section: 25 mm2 - 95 mm2, mounting type: NS 35/15, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type High current terminal block
Area of application Railway industry
Machine building
Plant engineering
Number of positions 1
Number of connections 2
Number of rows 1
Potentials 1
Data management status
Article revision 14
Insulation characteristics

Overvoltage category III
Degree of pollution 3
Electrical propertiesRated surge voltage 8 kV
Maximum power dissipation for nominal condition 7.54 W
Connection dataNumber of connections per level 2
Nominal cross section 95 mm²
Stripping length 40 mm
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 25 mm² ... 95 mm²
Cross section AWG 2 ... 3/0 (converted acc. to IEC)
Conductor cross section flexible 25 mm² ... 95 mm²
Conductor cross section, flexible [AWG] 2 ... 3/0 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 25 mm² ... 95 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 25 mm² ... 95 mm²
Cross-section with insertion bridge, rigid 70 mm²
Cross-section with insertion bridge, flexible 70 mm²
Nominal current 232 A
Maximum load current 232 A (with 95 mm² conductor cross section)
Nominal voltage 1000 V
Connection cross sections directly pluggable
Conductor cross section rigid 25 mm² ... 95 mm²
Conductor cross-section flexible (ferrule without plastic sleeve) 25 mm² ... 95 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 25 mm² ... 95 mm²
Ex dataRated data (ATEX/IECEx)
Identification ? II....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTPOWER 95 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.