INDUSTRIAL COMPONENT DATA

PTPOWER 95-F 3260133 PHOENIX CONTACT High-current terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTPOWER 95-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTPOWER 95-F
Catalog number	3260133
Category	Feed-through terminal block
Minimum order	3 Pcs
Document ID	EO-340785D1B9
Generated	2026-11-19

Product Overview

High-current terminal block
Current terminal, nominal voltage: 1000 V, nominal current: 232 A, number of connections: 2, number of poles: 1, connection type: PowerTurn connection, 1st floor, cross-section: 25 mm² - 95 mm², mounting class: direct screwed, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3260133
Packing unit 3 pc
Minimum order quantity 3 pc
Catalog page Page 129 (C-1-2017)
GTIN 4046356779036
Weight per Piece (excluding packing) 202.750 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of positions 1
Number of levels 1

Number of connections 2
Potentials 1
Nominal cross section 95 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 7.54 W
Maximum load current 232 A (with 95 mm2conductor cross section)
Nominal current IN 232 A
Nominal voltage UN 1000 V AC
1500 V DC
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 6 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 25 mm² / 4.5 kg
95 mm²/14 kg
Tensile test result Test passed
Conductor cross section tensile test 25 mm²
Tractive force setpoint...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTPOWER 95-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.