INDUSTRIAL COMPONENT DATA

# PTPOWER 95-FE-F 3260142 PHOENIX CONTACT High-current terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PTPOWER 95-FE-F**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PTPOWER 95-FE-F |
| Catalog number | 3260142 |
| Category | Feed-through terminal block |
| Minimum order | 3 Pcs |
| Document ID | EO-CEE0349512 |
| Generated | 2026-11-18 |

## Product Overview

High-current terminal block
Current terminal, nominal voltage: 1000 V, nominal current: 232 A, number of connections: 2, number of poles: 1, connection type: PowerTurn connection, 1st floor, cross-section: 25 mm² - 95 mm², mounting type: direct screwed, color: black/yellow

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Key Commercial Data
Orderkey 3260142
Packing unit 3 pc
Minimum order quantity 3 pc
Catalog page Page 129 (C-1-2017)
GTIN 4046356779067
Weight per Piece (excluding packing) 246.260 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of positions 1
Number of levels 1

Number of connections 2
Potentials 1
Nominal cross section 95 mm²
Color black/yellow
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 7.54 W
Maximum load current 232 A (with 95 mm2conductor cross section)
Nominal current IN 232 A
Nominal voltage UN 1000 V AC
1500 V DC
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTPOWER 95-FE-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.