INDUSTRIAL COMPONENT DATA

# EG 22,5-GMF/PC GN 2764797 PHOENIX CONTACT Electronic housing

**Brand: PHOENIX CONTACT | Manufacturer Part Number: EG 22,5-GMF/PC GN**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | EG 22,5-GMF/PC GN |
| Catalog number | 2764797 |
| Category | Extruded profile modular housing |
| Minimum order | 10 Pcs |
| Document ID | EO-153E22B06D |
| Generated | 2026-11-18 |

## Product Overview

Electronic housing
Housing, Bottom of the housing with metal pin, without ventilation slits, width: 22.5 mm, height: 75 mm, color: green (6021), cross bridge: without bus connector, number of poles cross connector: not relevant
Component housing, Lower housing part with metal foot catch, without vents, width: 22.5 mm, height: 75 mm, color: green (similar RAL 6021), cross connection: without bus connector, number of positions cross connector: not relevant

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Technical dataProduct propertiesProduct type Enclosure bottom part
Housing type Component housing
Housing series EG
Product family EG..-G
Type Lower housing part closed, housing cover necessary to complete the module
Number of positions 8
Max. number of positions 0)
Type Lower housing part with metal foot catch
Ventilation openings present no
Data management status
Article revision 05

DimensionsDimensional drawing
Width 22.5 mm
Height 75 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor (Housing) green (RAL 6021)
Flammability rating according to UL 94 V0
Housing material Polycarbonate
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Degree of protection IP20
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
PCB dataThickness of the PCB 1.4 mm ... 1.8 mm
MountingMounting type DIN rail mounting

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EG 22,5-GMF/PC GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.