INDUSTRIAL COMPONENT DATA

BC 53,6 OT U11 KMGY 2896416 PHOENIX CONTACT Upper part of housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 53,6 OT U11 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 53,6 OT U11 KMGY
Catalog number	2896416
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-A9A5C7F144
Generated	2026-11-19

Product Overview

Upper part of housing
Rail box for use in installation distributors according to DIN 43880, Top of the housing (U11) with ventilation slits, Installation depth of connection technology: 11.1 mm, width: 53.6 mm, height: 89.7 mm, depth: 49.78 mm, colour: light grey (7035)
DIN rail enclosure for use in installation distributors in accordance with DIN 43880, Enclosure top (U11) with ventilation slots, Recess depth of connection technology: 11.1 mm, width: 53.6 mm, height: 89.7 mm, depth: 49.78 mm, colour: light grey (similar to RAL 7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2896416
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 699 (C-1-2013)
GTIN 4046356103213
Weight per Piece (excluding packing) 24.090 g
Custom tariff number 85472000
Country of origin DE (Germany)
Item properties

Brief article description Upper part of housing
Type BC 53,6 OT U11 KMGY
Order No. 2896416
Housing type Installation component housing
Type Upper part
Dimensions
Width [w] 53.6 mm
Height [h] 89.7 mm
Depth [d] 49.78 mm
Material data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polycarbonate
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Packaging information
Pieces per package 10
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC000886ETIM 5.0EC001031ETIM 6.0EC001031
UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC 13.231261501

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 53,6 OT U11 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.