INDUSTRIAL COMPONENT DATA

ME MAX 6,2 SP-TBUS 4-4 KMGY 2869647 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 6,2 SP-TBUS 4-4 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 6,2 SP-TBUS 4-4 KMGY
Catalog number	2869647
Category	Electronic enclosure
Minimum order	10 Pcs
Document ID	EO-54D18949DD
Generated	2026-11-18

Product Overview

Electronic housing
Rail housing, Complete housing, tall design, with TBUS option, spring-mounted, width: 6.3 mm, height: 93.1 mm, depth: 101.2 mm, colour: light grey (7035), transverse bridge: Rail bus connector (optional)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2869647
Packing unit 10 pc
Note Made to Order (non-returnable)
Catalog page Page 683 (C-1-2013)
GTIN 4017918975142
Weight per Piece (excluding packing) 37.620 g
Custom tariff number 85369010
Country of origin DE (Germany)
Item properties
Brief article description Electronic housing
Type ME MAX 6,2 SP-TBUS 4-4 KMGY
Order No. 2869647

Housing type Complete housing
Type Tall design
Max. IP code to attain IP20
Mounting type DIN rail mounting
Number of levels 4
Ventilation openings present no
Max. number of positions 8 (pitch: 3.5 mm)
Dimensions
Dimensional drawing
Width [w] 6.2 mm
Height [h] 93.1 mm
Depth [d] 102.5 mm
Depth from top edge of DIN rail [d] 95 mm
Material data
Color (RAL) light gray
Housing material PBT
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
PCB data
Number of PCB holders 1
Mounting position Vertical (horizontal DIN rail)
Power dissipation, single housing at 20 °C
Mounting position vertical
Power dissipation, single housing at 30 °C
Mounting position vertical
Power dissipation, single housing at 40 °C
Mounting position vertical
Power dissipation, single housing at 50 °C
Mounting position vertical
Power dissipation, single housing at 60 °C
Mounting position vertical
General information
Type of note Assembly instruction:
Note...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 6,2 SP-TBUS 4-4 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.