INDUSTRIAL COMPONENT DATA

HS LC-H-D2C/ R4XC2-2,54 1071316 PHOENIX CONTACT Light guides, passive, rigid, can be used for the ME, ME-MAX..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HS LC-H-D2C/ R4XC2-2,54



Manufacturer	PHOENIX CONTACT
MPN / Reference	HS LC-H-D2C/ R4XC2-2,54
Catalog number	1071316
Category	Accessories/spare parts for industrial connectors
Minimum order	100 Pcs
Document ID	EO-A7639D26D1
Generated	2026-11-19

Product Overview

Light guides, passive, rigid, can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed)
Multi-light conductor with excessive radiation protection, passive, rigid, can be used for ME, ME MAX, ME-IO, ME PLC and EH device lines (case processing required)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1071316
Packing unit 1
GTIN 4055626752747
Custom tariff number 39269097
Product properties
Material specifications
General information
Standards and Regulations
Dimensions
Ambient conditions
Packaging details

Classifications
Product properties
Brief article description Fiber optic
Type HS LC-H-D2C/ R4XC2-2,54
Order No. 1071316
Type passive, rigid
Alignment Horizontal
Number of displays 8 (4 rows x 2 columns)
ESD protection < 8 kV
Head form Round, conical
Back to topDimensions
Pitch 2.54 mm
Diameter 2 mm
Hole diameter 1.2 mm
Back to topMaterial specifications
Material PC
Color (RAL) transparent
black (9005)
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
The tops of the press-in pegs are conical to make installation easier.
To prevent glare, the system has an aperture. This also makes mixed colors possible.
Back to topPackaging details
Pieces per package 100
Denomination packing units Pcs.
Back to topStandards and Regulations
Flammability rating according to UL 94 HB
Back to topClassifications
eCl@ss
eCl@ss 5.1 27180506
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
Back to topUNSPSC
UNSPSC 13.2 31261501
UNSPSC 18.0 31261501
UNSPSC 19.0 31261501
UNSPSC 20.0 31261501
UNSPSC 21.0 31261501....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HS LC-H-D2C/ R4XC2-2,54 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.