

**INDUSTRIAL COMPONENT DATA**

# HS LCA-RGB 10X3-L 1474405 PHOENIX CONTACT Signal light with braided wires, active, flexible, Lenticular head..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HS LCA-RGB 10X3-L



|                 |                                                                     |
|-----------------|---------------------------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                                     |
| MPN / Reference | HS LCA-RGB 10X3-L                                                   |
| Catalog number  | 1474405                                                             |
| Category        | Accessories/spare parts for optic and acoustic signalling equipment |
| Minimum order   | 1 Pcs                                                               |
| Document ID     | EO-2C02970050                                                       |
| Generated       | 2026-09-29                                                          |

## Product Overview

Signal light with braided wires, active, flexible, Lenticular head, radiant surface: spherical, number of indicators: 1, (1 row, 1 column), diameter: 10 mm

Signal light with braided wires, active, flexible

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Housing (HS)

## Additional Product Information

Technical dataNotesGeneral The light guide is designed to be pressed into an H7-tolerated receptacle. Dry-install the LED display by pressing it in vertically. As an alternative, you can glue in the LED display, e.g., using LOCTITE 460.

General Refer to the data sheet for the range in the download area.

Product propertiesProduct type Light

Number of positions 1

Alignment flexible

Type active, flexible

Conductor type Signal light with litz wires

Head form Raised head

Number of indicators 1 (1 row x 1 column)

DimensionsDiameter 10 mm (Aperture diameter)

3 mm (Lens diameter)

Hole diameter 8 mm

Dimensions 94 mm (Cable ends)  
Material specifications Color Linse transparent  
Color Gehäuse silver  
Insulating material PC  
Environmental and real-life conditions Ambient conditions  
Max. IP code to attain IP68  
Ambient temperature (operation) -20 °C ... 80 °C  
Packaging specifications Type of packaging PE bag

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HS LCA-RGB 10X3-L with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.