INDUSTRIAL COMPONENT DATA

VS-FSBPYS-OE-94H/0,5 SCO 1407504 PHOENIX CONTACT Flush-type socket

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-FSBPYS-OE-94H/0,5 SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-FSBPYS-OE-94H/0,5 SCO
Catalog number	1407504
Category	Circular connector, mounting (with cable)
Minimum order	10 Pcs
Document ID	EO-D4D8467EF8
Generated	2026-11-18

Product Overview

Flush-type socket
Conect. plug. to be apar. poster wall, Hybrid Ethernet CAT5 (100 MBit/s) CAT5 (100 MBit/s), 8-pole, Built-in mount female, straight, M12-SPEEDCON, encoding: Y, at free cable end, Rear mount, M16 x 1.5, Hybrid cable, cable length: 0.5 m, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1238749

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1407504
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 409 (C-2-2017)
GTIN 4046356807876
Weight per Piece (excluding packing) 74.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 0.5 m
Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C
-40 °C ... 85 °C (without mechanical actuation)
Degree of protection IP67
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 6 A (Power)
0.5 A (Data)
Rated voltage 60 V AC (Power and data)
60 V DC (Power and data)
Rated surge voltage 0.8 kV
Number of positions 8
Insulation resistance >= 100 M?
Coding Y - hybrid
Signal type/category Universal CAT5 (IEC 11801:2002)
Overvoltage category III
Degree of pollution 3
Connection method Cable connection
Insertion/withdrawal cycles > 100
Torque 2 Nm ... 3 Nm (Installation-side)
Mounting type Rear mounting M16 x 1.5
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PPA
Material, knurls Zinc die-cast, nickel-plated
Sealing material FKM
Standards and Regulations
Flammability rating according to UL 94....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-FSBPYS-OE-94H/0,5 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.