INDUSTRIAL COMPONENT DATA

IB IL 24 PSDOR 4-F-PAC 2700563 PHOENIX CONTACT Safety module

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL 24 PSDOR 4-F-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL 24 PSDOR 4-F-PAC
Catalog number	2700563
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-A9A611C39B
Generated	2026-11-18

Product Overview

Safety module
Safety-oriented, IP20-rated decentralised relay output module for the PROFIsafe system. The module has 4 safe relay outputs with 2 contacts each. Output states are reproduced for diagnostic purposes.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data
Orderkey 2700563
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356583169
Weight per Piece (excluding packing) 462.800 g
Custom tariff number 85371098
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 73.2 mm
Height 119.8 mm

Depth 71.5 mm
Note on dimensions Housing dimensions
Ambient conditions
Ambient temperature (operation) -25 °C ... 55 °C
Ambient temperature (storage/transport) -25 °C ... 70 °C
Permissible humidity (operation) 10 % ... 85 % (Take suitable measures against increased air humidity within the permitted temperature range.)
Permissible humidity (storage/transport) 10 % ... 85 % (Take suitable measures against increased air humidity within the permitted temperature range.)
Air pressure (operation) 80 kPa ... 108 kPa (up to 2000 m above sea level)
Air pressure (storage/transport) 66 kPa ... 108 kPa (up to 3500 m above sea level)
Degree of protection IP20
General
Mounting type DIN rail
Net weight 462.8 g
Note on weight specifications with connectors
Interfaces
Designation Inline local bus
No. of channels 2
Connection method Inline data jumper
Transmission speed 500 kbps / 2 Mbps (can be switched)
Power supply for module electronics
Supply voltage 24 V DC (via voltage jumper)
Supply voltage range 19.2 V DC ... 30 V DC
Inline potentials
Designation Communications power (UL)
Supply voltage 7.5 V DC (see safety data)
Current consump...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL 24 PSDOR 4-F-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.