

INDUSTRIAL COMPONENT DATA

ICC20-TS2,5/3L5,0-7035 1380485 PHOENIX CONTACT Printed circuit board terminal, rated current: 24 A, rated vo..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICC20-TS2,5/3L5,0-7035

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ICC20-TS2,5/3L5,0-7035
Catalog number	1380485
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-6136D5BE60
Generated	2026-09-29

Product Overview

Printed circuit board terminal, rated current: 24 A, rated voltage (III/2): 300 V, rated cross-section: 2.5 mm², number of potentials: 3, number of rows: 1, number of poles per row: 3, article family: ICC.. -TS2.5/.. L5.0, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping method: H1L Philipps-Recess with longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: light gray, Pin arrangement: Linear pin arrangement, number of solder pins per potential: 1, Packaging Type: Boxed Packaging. Item with side pin output on the left

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICC20-TS2,5/3L5,0-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.