INDUSTRIAL COMPONENT DATA

ICC25-H/4L5,0-6021 1207794 PHOENIX CONTACT Printed circuit board base housing, nominal section: 2.5 mm2, col..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICC25-H/4L5,0-6021

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ICC25-H/4L5,0-6021
Catalog number	1207794
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-196ECAE4D9
Generated	2026-11-18

Product Overview

ICC25-H/4L5,0-6021 1207794 PHOENIX CONTACT Printed circuit board base housing, nominal section: 2.5 mm2, col..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	**Fixed connector**
Contact type (EF001587)	**Pin**
Number of poles (EF001391)	**4**
Number of plug-in contact rows (EF006935)	**1**
Modular spacing contacts (EF007326)	**5 mm**
Modular spacing connections (EF006827)	**5 mm**
Rated current In (EF008250)	**16 A**
Rated voltage (EF000228)	**320 V**
Rated surge voltage (EF002993)	**4 kV**
Over voltage category (EF006785)	**III**
Pollution degree (EF006786)	**2**
Material of contact surface (EF004020)	**Tin**
Type of electric connection (EF003961)	**Other**
Diameter connection pin (EF006823)	**1.4 mm**
Length pin (EF006825)	**3.5 mm**

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Material insulation body (EF007543)	**Other**
Housing colour (EF000136)	**Green**
Inflammability class of insulation material according to UL94 (EF002521)	**V0**
Operating temperature (EF002393)	**-40 °C**
Type of fastening (EF002442)	**Other**

Classification & Catalog Path

Catalog path	**PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Printed circuit board base housing, nominal section: 2.5 mm2, color: green, nominal current: 16 A, nominal voltage (III/2): 320 V, contact surface: Sn, contact connection type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, article family: ICC.. -H/.. L5.0, pitch: 5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of welding pins per potential: 1, plug-in system: ICC 2.5, Plug-in face orientation: Standard, locking: Snap-in lock, clamping type: without, packaging type: Carton packing, Item with pin l output Base housing printed circuit board, nominal section: 2.5 mm², color: green, rated current: 16 A, sizing voltage (III/2): 320 V, contact type: Male, number of potentials: 4, Number of rows: 1, Number of poles per row: 4, number of connections: 4, article family: ICC. -H/.. L5.0, pitch: 5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, Plug-in face orientation: Standard, Locking: Lace lock, fixing type: sin, packing type: Carton packaging,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICC25-H/4L5,0-6021 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.