INDUSTRIAL COMPONENT DATA

ICC25-H/4R5,0-5015 1071449 PHOENIX CONTACT PCB headers, number of positions: 4, pitch: 5 mm, color: sky blue..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICC25-H/4R5,0-5015



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICC25-H/4R5,0-5015
Catalog number	1071449
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-7B4A28A775
Generated	2026-11-19

Product Overview

PCB headers, number of positions: 4, pitch: 5 mm, color: sky blue, solder pin [P]: 3.5 mm, Article with lateral pin exit Printed circuit board base housing, nominal section: 2.5 mm², color: blue, nominal current: 16 A, nominal voltage (III/2): 320 V, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, article family: ICC.. -H/.. R5.0, pitch: 5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of welding pins per potential: 1, Plug-in face orientation: Standard, locking: Snap lock, fixing type: without, packaging type: Carton packing, Item with right side pin output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1071449
Packing unit 1 pc
Minimum order quantity 50 pc
GTIN 4055626751788
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85366930
Country of origin PL (Poland)
Drawings
General

Classifications
Dimensions
Standards and Regulations
Drawings
Diagram
Type: PSPT 2,5/...-ST ... with ICC20(25)-H/...L(R)5,0-...
Diagram
Type: MSTBT 2,5 HC/...-STF with ICC20(25)-H/...L(R)5,0-...
Back to topDimensions
Length [l] 20.35 mm
Width 25 mm
Pitch 5 mm
Width [w] 25 mm
Height [h] 22.4 mm
Length of the solder pin 3.5 mm
Length 20.35 mm
Back to topGeneral
Range of articles ICC25-H/..R
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/2) 320 V
Rated voltage (II/2) 630 V
Insulating material PA
Flammability rating according to UL 94 V0
Color sky blue
Number of positions 4
Back to topStandards and Regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 5.1 27260700
eCl@ss 6.0 27260700
eCl@ss 7.0 27440402
eCl@ss 8.0 27440402
eCl@ss 9.0 27440402
Back to topETIM
ETIM 5.0 EC002637
ETIM 6.0 EC002637
ETIM 7.0 EC002637
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICC25-H/4R5,0-5015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.