INDUSTRIAL COMPONENT DATA

ICS20-C100X12-7035 2203879 PHOENIX CONTACT Upper part of housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS20-C100X12-7035

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS20-C100X12-7035
Catalog number	2203879
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-A61404BDBF
Generated	2026-11-18

Product Overview

Upper part of housing
Rail box, Top, closed, width: 20 mm, height: 100 mm, depth: 14.35 mm, colour: light grey (7035)
DIN rail enclosures, top, closed, width: 20 mm, height: 100 mm, depth: 14.35 mm, colour: light grey (similar to RAL 7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203879
Packing unit 10 pc
Minimum order quantity 10 pc
GTIN 4055626465548
Weight per Piece (excluding packing) 6.200 g
Custom tariff number 85389099
Country of origin DE (Germany)
Item properties
Brief article description Upper part of housing
Type ICS20-C100X12-7035
Order No. 2203879
Housing type Component housing

Type Upper part
Dimensions
Width [w] 20 mm
Height [h] 100 mm
Depth [d] 12 mm
Material data
Housing material PA 6.6
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 100 °C (observe derating)
Mechanical strength/tumbling barrel
Height of fall 50 cm
Number of drop cycles 50
Thermostability (Ball Thrust Test)
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20
Test for assessing the risk of fire (glow wire)
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Test for substances that would hinder coating with paint or varnish
Specification VW PV 3.10.7:2005-02
Packaging information
Pieces per package 10
Denomination packing units Pcs.
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127180505eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 5.0EC001031ETIM 6.0EC001031

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS20-C100X12-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.