INDUSTRIAL COMPONENT DATA

ICS20-F22U-1018 1287385 PHOENIX CONTACT Rail box, ICS plug, with USB open section, width: 20 mm, height: 7.2..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS20-F22U-1018



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS20-F22U-1018
Catalog number	1287385
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-09258A05D3
Generated	2026-11-19

Product Overview

Rail box, ICS plug, with USB open section, width: 20 mm, height: 7.25 mm, depth: 22.4 mm, colour: yellow (Similar RAL 1018)
Mounting Rail Enclosures, Filler ICS, with USB Functional Opening, Width: 20 mm, Height: 7.25 mm, Depth: 22.4 mm, Color: Yellow (1018)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataNotesGeneral notes Please refer to the data sheet of the product series in the download area.
Article featuresProduct Type Connections panel
Product Family ICS20
Execution ICS filler, with USB functional opening
Enclosure type Mounting Rail Enclosures
Ventilation opening available no
Enclosure Series ICS
Connection dataConductor cross-section AWG (converted according to IEC)
dimensionsDimensioned Drawing
width 20 mm
height 7.25 mm
Depth 22.4 mm

Printed circuit board design
Printed circuit board thickness 1.4 mm ... 1.8 mm
Material informationColor Yellow (1018)
Combustibility class according to UL 94 V0
CTI according to IEC 60112 600
Surface Finish untreated
Housing Material Polyamide
Environmental and electrical life conditionsVibration test
Test Specification DIN EN 60068-2-6 (VDE 0468-2-6):2008-10
Frequency 10 - 150 - 10 Hz
Sweep Speed 1 octave/min
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)
Acceleration 2g (58.1 Hz ... 150 Hz)
Test duration per axle 2.5 h
Test Directions X, Y, and Z axis
Glow Wire Test
Test Specification DIN EN 60695-2-11 (VDE 0471-2-11):2014-11
Temperature 850 °C
Duration of application 30 s
Heat Resistance / Ball Pressure Test
Test Specification DIN EN 60695-10-2 (VDE 0471-10-2):2016-01
Temperature 125 °C
Trial duration 1 h
Force 20 N
Mechanical Strength / Rotating Drum
Test Specification DIN EN 60068-2-31 (VDE 0468-2-31):2009-04
Fall Height 50 cm
Frequency 50
Shock
Test Specification DIN EN 60068-2-27 (VDE 0468-2-27):2010-02
Shock Form Semi-si...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS20-F22U-1018 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.