INDUSTRIAL COMPONENT DATA

ICS20-F45V-7035 1079493 PHOENIX CONTACT DIN rail housing, ICS filler, with vents, width: 20 mm, height: 7 mm..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS20-F45V-7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS20-F45V-7035
Catalog number	1079493
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-0E60BEBB6C
Generated	2026-11-19

Product Overview

DIN rail housing, ICS filler, with vents, width: 20 mm, height: 7 mm, depth: 45 mm, color: light gray (7035)
Rail box, ICS plug, with ventilation slits, width: 20 mm, height: 7.25 mm, depth: 44.9 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1079493
Packing unit 1
GTIN 4055626799926
Custom tariff number 85389099
Item properties
Material data
General information
Standards and regulations
Dimensions
Ambient conditions
Packaging information
Classifications
Item properties

Brief article description Connection plate
Type ICS20-F45V-7035
Order No. 1079493
Housing type DIN rail housing
Type ICS filler, with vents
Mounting type Slot
Ventilation openings present yes
Back to topDimensions
Width [w] 20 mm
Height [h] 7 mm
Depth [d] 45 mm
Back to topMaterial data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Back to topPackaging information
Pieces per package 10
Denomination packing units Pcs.
Outer packaging type Resealable bag
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 5.1 27180506
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS20-F45V-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.