INDUSTRIAL COMPONENT DATA

ICS25-B122X98-V-7035 2203885 PHOENIX CONTACT Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-B122X98-V-7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-B122X98-V-7035
Catalog number	2203885
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-F87DD47CFA
Generated	2026-11-18

Product Overview

Mounting base housing
Rail housing, Housing underside with metal pin, Level 1: with ventilation slits, width: 25 mm, height: 122.5 mm, depth: 108.35 mm, colour: light grey (7035), cross bridge: Rail bus connector (optional), number of cross connector poles: 8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203885
Packing unit 10 pc
Minimum order quantity 10 pc
GTIN 4055626465906
Weight per Piece (excluding packing) 57.200 g
Custom tariff number 85389099
Country of origin DE (Germany)
Item properties
Brief article description Mounting base housing
Type ICS25-B122X98-V-7035
Order No. 2203885
Housing type

Type Lower part
Ventilation openings present yes
Dimensions
Width [w] 25 mm
Height [h] 122 mm
Depth from top edge of DIN rail [d] 98 mm
Dimensions 25 mm x 122 mm x 110 mm (Lower housing part with upper housing part)
Material data
Color (similar to RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material PA 6.6
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 100 °C (observe derating)
PCB data
Number of PCB holders 2
Power dissipation, single housing at 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 17 W
Power dissipation, single housing at 30 °C
Ambient temperature 40 °C
Reduction factor 0.67
Mounting position vertical
Power dissipation, single housing at 40 °C
Ambient temperature 60 °C
Reduction factor 0.41
Mounting position vertical
Power dissipation, single housing at 50 °C
Ambient temperature 80 °C
Reduction factor 0.22
Mounting position vertical
Mechanical strength/tumbling barrel
Height of fall 50 cm
Number of drop cycles 50
Vibration test
Specifica...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-B122X98-V-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.