INDUSTRIAL COMPONENT DATA

# ICS25-B122X98-V-9005 1072526 PHOENIX CONTACT DIN rail housing, Lower housing part with metal foot catch, Lev..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-B122X98-V-9005**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | ICS25-B122X98-V-9005 |
| Catalog number | 1072526 |
| Category | Extruded profile modular housing |
| Minimum order | 10 Pcs |
| Document ID | EO-6FF47EC18A |
| Generated | 2026-11-19 |

## Product Overview

DIN rail housing, Lower housing part with metal foot catch, Level 1: with vents, width: 25 mm, height: 122 mm, number of positions cross connector: not relevant, color: black (9005)
Rail housing, Bottom of housing with metal pin, Level 1: with ventilation slits, width: 25 mm, height: 122.5 mm, depth: 108.35 mm, color: black (9005), cross bridge: Rail bus connector (optional), number of poles cross connector: 8

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Key Commercial Data
Orderkey 1072526
Packing unit 1
GTIN 4055626765518
Custom tariff number 85389099
Drawings
Dimensions
Ambient conditions
Mechanical strength/tumbling barrel
Shock
Test for assessing the risk of fire (glow wire)
Degrees of protection provided by housings (IP code)

General information
Standards and regulations
Item properties
Material data
PCB data
Vibration test
Thermostability (Ball Thrust Test)
Test for substances that would hinder coating with paint or varnish
Protection against electric shock
Packaging information
Classifications
Drawings
Dimensional drawing
Back to topItem properties
Brief article description Mounting base housing
Type ICS25-B122X98-V-9005
Order No. 1072526
Housing type DIN rail housing
Type Lower housing part with metal foot catch
Max. IP code to attain IP20
Mounting type DIN rail mounting
Number of levels 4
Connection levels 3 (Both sides)
Ventilation openings present yes
Max. number of positions 24 (pitch: 5 mm)
30 (pitch: 3.5 mm)
Back to topDimensions
Dimensional drawing
Width [ w ] 25 mm
Height [ h ] 122 mm
Depth from top edge of DIN rail [ d ] 98 mm
Dimensions 25 mm x 122 mm x 110 mm (Lower housing part with upper housing part)
Back to topMaterial data
Color (RAL) black (9005)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (de...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-B122X98-V-9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.