INDUSTRIAL COMPONENT DATA

# ICS25-B77X75-O-7035 2203876 PHOENIX CONTACT Mounting base housing

**Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-B77X75-O-7035**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | ICS25-B77X75-O-7035 |
| Catalog number | 2203876 |
| Category | Extruded profile modular housing |
| Minimum order | 10 Pcs |
| Document ID | EO-46B4891649 |
| Generated | 2026-11-18 |

## Product Overview

Mounting base housing
Rail housing, Housing underside with metal pin, width: 25 mm, height: 77.5 mm, depth: 85.8 mm, colour: light grey (7035), cross bridge: Rail bus connector (optional), number of poles cross connector: 8

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Key Commercial Data
Orderkey 2203876
Packing unit 10 pc
Minimum order quantity 10 pc
GTIN 4055626465517
Weight per Piece (excluding packing) 30.490 g
Custom tariff number 85389099
Country of origin DE (Germany)
Item properties
Brief article description Mounting base housing
Type ICS25-B77X75-O-7035
Order No. 2203876
Housing type

Type Lower part
Dimensions
Width [ w ] 25 mm
Height [ h ] 77 mm
Depth from top edge of DIN rail [ d ] 75 mm
Dimensions 25 mm x 77 mm x 87 mm (Lower housing part with upper housing part)
Material data
Color (similar to RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material PA 6.6
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 100 °C (observe derating)
PCB data
Number of PCB holders 2
Power dissipation, single housing at 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 17 W
Power dissipation, single housing at 30 °C
Ambient temperature 40 °C
Reduction factor 0.67
Mounting position vertical
Power dissipation, single housing at 40 °C
Ambient temperature 60 °C
Reduction factor 0.41
Mounting position vertical
Power dissipation, single housing at 50 °C
Ambient temperature 80 °C
Reduction factor 0.22
Mounting position vertical
Mechanical strength/tumbling barrel
Height of fall 50 cm
Number of drop cycles 50
Vibration test
Specification IEC 60068-2-6:2007-12
Frequency....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-B77X75-O-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.